Docket No. R.305913

Preliminary Amdt.

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

Listing of Claims:

Claims 1-9. (Canceled)

10. (New) In an inlet valve assembly of a high-pressure fuel pump comprising a valve

element disposed in a valve chamber and a fluid conduit adjoining the valve chamber on the

upstream side, the improvement wherein the fluid conduit is embodied such that a rotation

(swirl) about the longitudinal axis of the fluid conduit is impressed on the fluid stream that

flows toward the valve chamber.

11. (New) The valve assembly as recited in claim 10, wherein the fluid conduit comprises a

first conduit portion and a second conduit portion adjoining the first conduit portion, the

longitudinal axes of the first and second conduit portions being at an angle < 180° to one

another, and the longitudinal axis of the first conduit portion being laterally offset from the

longitudinal axis of the second conduit portion.

12. (New) The valve assembly as recited in claim 11, wherein the longitudinal axes of the

first and second conduit portions are at least approximately at a right angle to one another.

Page 6 of 11

Docket No. R.305913 Preliminary Amdt.

13. (New) The valve assembly as recited in claim 10, further comprising a ball or a cone element as the valve element.

14. (New) The valve assembly as recited in claim 11, further comprising a ball or a cone element as the valve element.

15. (New) The valve assembly as recited in claim 12, further comprising a ball or a cone element as the valve element.

16. (New) The valve assembly as recited in claim 11, wherein the first and second conduit portions, in cross section, have at least approximately the same radius; and wherein the lateral offset of the longitudinal axes is greater than the radius.

17. (New) The valve assembly as recited in claim 12, wherein the first and second conduit portions, in cross section, have at least approximately the same radius; and wherein the lateral offset of the longitudinal axes is greater than the radius.

18. (New) The valve assembly as recited in claim 13, wherein the first and second conduit portions, in cross section, have at least approximately the same radius; and wherein the lateral offset of the longitudinal axes is greater than the radius.

Docket No. R.305913 Preliminary Amdt.

- 19. (New) The valve assembly as recited in claim 11, further comprising a transition region between the first conduit portion and the second conduit portion, the transition region being machined by means of electrochemical removal of material.
- 20. (New) The valve assembly as recited in claim 12, further comprising a transition region between the first conduit portion and the second conduit portion, the transition region being machined by means of electrochemical removal of material.
- 21. (New) The valve assembly as recited in claim 13, further comprising a transition region between the first conduit portion and the second conduit portion, the transition region being machined by means of electrochemical removal of material.
- 22. (New) The valve assembly as recited in claim 16, further comprising a transition region between the first conduit portion and the second conduit portion, the transition region being machined by means of electrochemical removal of material.
- 23. (New) The valve assembly as recited in claim 19, wherein the transition region comprises a wall that is curved from the first conduit portion to the second conduit portion.
- 24. (New) The valve assembly as recited in claim 20, wherein the transition region comprises a wall that is curved from the first conduit portion to the second conduit portion.

Docket No. R.305913 Preliminary Amdt.

- 25. (New) The valve assembly as recited in claim 21, wherein the transition region comprises a wall that is curved from the first conduit portion to the second conduit portion.
- 26. (New) The valve assembly as recited in claim 22, wherein the transition region comprises a wall that is curved from the first conduit portion to the second conduit portion.
- 27. (New) The valve assembly as recited in claim 11, wherein the first conduit portion extends no more than an axially insignificantly distance past the second conduit portion.
- 28. (New) The valve assembly as recited in claim 10, wherein the longitudinal axis of the first conduit portion and the longitudinal axis of the second conduit portion form an angle > 90°.
- 29. (New) The valve assembly as recited in claim 11, wherein the longitudinal axis of the first conduit portion and the longitudinal axis of the second conduit portion form an angle > 90°.